

Sieving for pseudosquares and pseudocubes in parallel using doubly-focused enumeration and wheel datastructures^{*}

Jonathan P. Sorenson

Butler University, Indianapolis IN 46208, USA,
sorenson@butler.edu,
<http://www.butler.edu/~sorenson>

Abstract. We extend the known tables of pseudosquares and pseudocubes, discuss the implications of these new data on the conjectured distribution of pseudosquares and pseudocubes, and present the details of the algorithm used to do this work. Our algorithm is based on the space-saving wheel data structure combined with doubly-focused enumeration, run in parallel on a cluster supercomputer.

1 Introduction

It is well-known that testing for primality can be done in polynomial time [1,3]. However, the fastest known deterministic algorithms are conjectured to be the pseudosquares prime test of Lukes, Patterson, and Williams [6], and its generalization, the pseudocube prime test of Berrizbeitia, Müller, and Willimas [4], both of which run in roughly cubic time, if a sufficiently large pseudosquare or pseudocube is available. In particular, the pseudosquares prime test is very useful in the context of finding all primes in an interval [9], where sieving can be used in place of trial division. This, then, motivates the search for larger and larger pseudosquares and pseudocubes, and attempts to predict their distribution. See, for example, Wooding and Williams [12] and also [7,11,8,2,10].

In this paper, we present extensions to the known tables of pseudosquares and pseudocubes in §2. We discuss the implications of this new data on the conjectured distribution of pseudosquares and pseudocubes in §3, and give a minor refinement of the current conjectures. Then we describe our parallel algorithm, based on Bernstein's doubly-focused enumeration [2], which is used in a way similar, but not identical to the work of Wooding and Williams [12], combined with the space-saving wheel data structure presented in [9, §4.1]. We then suggest ideas for future work in §5.

^{*} Supported by a grant from the Holcomb Awards Committee, and computing resources provided by the Frank Levinson Supercomputing Center at Butler University.

2 Computational Results

Let (x/y) denote the Legendre symbol [5]. For an odd prime p , let $L_{p,2}$, the *pseudosquare* for p , be the smallest positive integer such that

1. $L_{p,2} \equiv 1 \pmod{8}$,
2. $(L_{p,2}/q) = 1$ for every odd prime $q \leq p$, and
3. $L_{p,2}$ is not a perfect square.

In other words, $L_{p,2}$ is a square modulo all primes up to p , but is not a square. We found the following new pseudosquares:

p	$L_{p,2}$
367	36553 34429 47705 74600 46489
373	42350 25223 08059 75035 19329
379	$> 10^{25}$

The two pseudosquares listed were found in 2008 in a computation that went up to 5×10^{24} , taking roughly 3 months wall time. The final computation leading to the lower bound of 10^{25} ran for about 6 months, in two 3-month pieces, the second of which finished on January 1st, 2010.

Wooding and Williams [12] had found a lower bound of $L_{367,2} > 120120 \times 2^{64} \approx 2.216 \times 10^{24}$. (Note: a complete table of pseudosquares, current as of this writing, is available at <http://cr.yp.to/focus.html> care of Dan Bernstein).

Similarly, for an odd prime p , let $L_{p,3}$, the *pseudocube* for p , be the smallest positive integer such that

1. $L_{p,3} \equiv \pm 1 \pmod{9}$,
2. $L_{p,3}^{(q-1)/3} \equiv 1 \pmod{q}$ for every prime $q \leq p$, $q \equiv 1 \pmod{3}$,
3. $\gcd(L_{p,3}, q) = 1$ for every prime $q \leq p$, and
4. $L_{p,3}$ is not a perfect cube.

We found the following new pseudocubes (only listed for $p \equiv 1 \pmod{3}$):

p	$L_{p,3}$
499	601 25695 21674 16551 89317
523,541	1166 14853 91487 02789 15947
547	41391 50561 50994 78852 27899
571,577	1 62485 73199 87995 69143 39717
601,607	2 41913 74719 36148 42758 90677
613	67 44415 80981 24912 90374 06633
619	$> 10^{27}$

These pseudocubes were found in about 6 months of total wall time in 2009. Wooding and Williams [12] had found a lower bound of $L_{499,3} > 1.45152 \times 10^{22}$. For a complete list of known pseudocubes, see [12,4,10].

3 The Distribution of Pseudosquares and Pseudocubes

Let p_i denote the i th prime, and q_i denote the i th prime such that $q_i \equiv 1 \pmod{3}$. In [6] it was conjectured that, for a constant $c_2 > 0$, we have

$$L_{p_n,2} \approx c_2 2^n \log p_n. \quad (1)$$

Using similar methods, in [4] it was conjectured that, for a constant $c_3 > 0$, we have

$$L_{q_n,3} \approx c_3 3^n (\log q_n)^2. \quad (2)$$

In a desire to test the accuracy of these conjectures, for integers $n > 0$ let us define

$$c_2(n) := \frac{L_{p_n,2}}{2^n \log p_n}, \quad (3)$$

$$c_3(n) := \frac{L_{q_n,3}}{3^n (\log q_n)^2}. \quad (4)$$

We calculated $c_2(n)$ and $c_3(n)$ from known pseudosquares and pseudocubes. We present these computations in Table 1, for pseudosquares, and in Table 2, for pseudocubes, below.

From Table 1, we readily see that $c_2(n)$ appears to be bounded between roughly 5 and 162, with an average value near 45. There is no clear trend toward zero or infinity. Due to the common occurrence of values of n where $L_{p_n,2} = L_{p_{n+1},2}$ (for example, $n = 56$), it should also be clear $c_2(n)$ does not have a limit.

Similarly for the pseudocubes, in Table 2 we see that $0.05 < c_3(n) < 6.5$ for $10 \leq n \leq 53$, with an average value of roughly 1.22. And again, there is no clear trend toward zero or infinity, nor can there be a limit for $c_3(n)$.

This leads us to the following refinements, if you will, of the conjectures (1),(2) above.

Conjecture. For the pseudosquares, we conjecture that

$$\liminf_{n \rightarrow \infty} \frac{L_{p_n,2}}{2^n \log p_n} > 0, \quad (5)$$

$$\limsup_{n \rightarrow \infty} \frac{L_{p_n,2}}{2^n \log p_n} < \infty. \quad (6)$$

Similarly, for the pseudocubes, we conjecture that

$$\liminf_{n \rightarrow \infty} \frac{L_{q_n,3}}{3^n (\log q_n)^2} > 0, \quad (7)$$

$$\limsup_{n \rightarrow \infty} \frac{L_{q_n,3}}{3^n (\log q_n)^2} < \infty. \quad (8)$$

Our data also has implications on the relative efficiency of primality testing. In particular, several researchers have pointed out that if conjectures (1),(2) are

Table 1. Values of $c_2(n)$ based on known pseudosquares.

n	p_n	$L_{p_n,2}$	$c_2(n)$	n	p_n	$L_{p_n,2}$	$c_2(n)$
2	3	73	16.61	39	167	112434732901969	39.96
3	5	241	18.72	40	173	178936222537081	31.58
4	7	1009	32.41	41	179	178936222537081	15.69
5	11	2641	34.42	42	181	696161110209049	30.45
6	13	8089	49.28	43	191	696161110209049	15.07
7	17	18001	49.64	44	193	2854909648103881	30.84
8	19	53881	71.48	45	197	6450045516630769	34.70
9	23	87481	54.49	46	199	6450045516630769	17.32
10	29	117049	33.95	47	211	11641399247947921	15.46
11	31	515761	73.34	48	223	11641399247947921	7.65
12	37	1083289	73.24	49	227	190621428905186449	62.42
13	41	3206641	105.41	50	229	196640148121928601	32.14
14	43	3818929	61.97	51	233	712624335095093521	58.06
15	47	9257329	73.38	52	239	1773855791877850321	71.92
16	53	22000801	84.55	53	241	2327687064124474441	47.12
17	59	48473881	90.70	54	251	6384991873059836689	64.15
18	61	48473881	44.98	55	257	8019204661305419761	40.11
19	67	175244281	79.49	56	263	10198100582046287689	25.40
20	71	427733329	95.70	57	269	10198100582046287689	12.65
21	73	427733329	47.54	58	271	10198100582046287689	6.32
22	79	898716289	49.04	59	277	69848288320900186969	21.54
23	83	2805544681	75.69	60	281	208936365799044975961	32.14
24	89	2805544681	37.25	61	283	533552663339828203681	40.99
25	97	2805544681	18.28	62	293	936664079266714697089	35.76
26	101	10310263441	33.29	63	307	936664079266714697089	17.73
27	103	23616331489	37.96	64	311	2142202860370269916129	20.23
28	107	85157610409	67.89	65	313	2142202860370269916129	10.10
29	109	85157610409	33.81	66	317	2142202860370269916129	5.04
30	113	196265095009	38.67	67	331	13649154491558298803281	15.94
31	127	196265095009	18.87	68	337	34594858801670127778801	20.14
32	131	2871842842801	137.15	69	347	99492945930479213334049	28.81
33	137	2871842842801	67.95	70	349	99492945930479213334049	14.39
34	139	2871842842801	33.88	71	353	295363187400900310880401	21.32
35	149	26250887023729	152.68	72	359	295363187400900310880401	10.63
36	151	26250887023729	76.14	73	367	3655334429477057460046489	65.54
37	157	112434732901969	161.79	74	373	4235025223080597503519329	37.86
38	163	112434732901969	80.30				

Table 2. Values of $c_3(n)$ based on known pseudocubes.

n	q_n	$L_{q_n,3}$	$c_3(n)$	n	q_n	$L_{q_n,3}$	$c_3(n)$
10	79	7235857	6.42	32	337	75017625272879381	1.2
11	97	8721539	2.35	33	349	75017625272879381	0.394
12	103	8721539	0.764	34	367	996438651365898469	1.71
13	109	91246121	2.6	35	373	2152984914389968651	1.23
14	127	91246121	0.813	36	379	12403284862819956587	2.34
15	139	98018803	0.281	37	397	37605274105479228611	2.33
16	151	1612383137	1.49	38	409	37605274105479228611	0.77
17	157	1612383137	0.488	39	421	37605274105479228611	0.254
18	163	7991083927	0.795	40	433	205830039006337114403	0.459
19	181	7991083927	0.254	41	439	1845193818928603436441	1.37
20	193	7991083927	0.0827	42	457	7854338425385225902393	1.91
21	199	20365764119	0.0695	43	463	12904554928068268848739	1.04
22	211	2515598768717	2.8	44	487	13384809548521227517303	0.355
23	223	6440555721601	2.34	45	499	60125695216741655189317	0.527
24	229	29135874901141	3.49	46	523	116614853914870278915947	0.336
25	241	29135874901141	1.14	47	541	116614853914870278915947	0.111
26	271	29135874901141	0.365	48	547	4139150561509947885227899	1.31
27	277	406540676672677	1.69	49	571	16248573199879956914339717	1.69
28	283	406540676672677	0.558	50	577	16248573199879956914339717	0.56
29	307	406540676672677	0.181	51	601	24191374719361484275890677	0.274
30	313	406540676672677	0.0598	52	607	24191374719361484275890677	0.0912
31	331	75017625272879381	3.61	53	613	674441580981249129037406633	0.845

true, then the running time of the pseudocube prime test, which depends on the value of $L_{q_n,3}^{2/3}$, should eventually outperform the pseudosquare prime test, whose running time depends on $L_{p_n,2}$. In particular, one infers from conjectures (1) and (2) that

$$\frac{L_{q_n,3}^{2/3}}{L_{p_n,2}} \gg \left(\frac{3^{2/3}}{2}\right)^n > 1 \quad (9)$$

for sufficiently large n (see [12, §9.1]). This inference follows from our refined conjectures as well.

We have our first specific value of n to support (9), namely with $n = 48$, where $L_{q_n,3}^{2/3} \approx 2.214 \cdot L_{p_n,2}$. However, given that $c_2(n)$ averages about 45, and $c_3(n)$ averages just over 1.2, we would reasonably expect (9) to largely be true only for n larger than about 75, under the assumption these averages are maintained. To test this, more pseudosquares and, in particular, more pseudocubes are needed.

4 Algorithm Details

We begin with a review of doubly-focused enumeration, explain how we employ parallelism, and how the space-saving wheel datastructure is utilized. We also discuss the details of our implementation, including the hardware platform and software used.

4.1 Doubly-Focused Enumeration

The main idea is that every integer x , with $0 \leq x \leq H$, can be written in the form

$$x = t_p M_n - t_n M_p \quad (10)$$

where

$$\gcd(M_p, M_n) = 1, \quad 0 \leq t_p \leq \frac{H + M_n M_p}{M_n}, \quad \text{and} \quad 0 \leq t_n < M_n. \quad (11)$$

(See [2] or [12, Lemma 1].) This is an explicit version of the Chinese Remainder Theorem.

To find pseudosquares, we set M_n and M_p to be products of small odd primes and 8, choose t_p to be square modulo M_p , and $-t_n$ to be square modulo M_n . To be precise, in our implementation we set

$$\begin{aligned} M_p &= 7 \cdot 11 \cdot 13 \cdot 17 \cdot 19 \cdot 23 \cdot 29 \cdot 31 \cdot 37 \cdot 41 \cdot 43 \cdot 53 \cdot 89 \\ &= 2057\,04617\,33829\,17717 \quad \text{and} \\ M_n &= 8 \cdot 3 \cdot 5 \cdot 47 \cdot 59 \cdot 61 \cdot 67 \cdot 71 \cdot 73 \cdot 79 \cdot 83 \cdot 97 \\ &= 4483\,25952\,77215\,26840. \end{aligned}$$

Note that both $M_p, M_n < 2^{64}$, allowing us to work in 64-bit machine arithmetic.

To find pseudocubes, the same idea applies, only note that if $-t_n$ is a cube modulo M_n , so is t_n . We used only 2, 9 and primes congruent to 1 (mod 3) for better filter rates:

$$\begin{aligned} M_p &= 2 \cdot 7 \cdot 13 \cdot 31 \cdot 43 \cdot 73 \cdot 79 \cdot 127 \cdot 139 \cdot 157 \cdot 181 \\ &= 701\,856\,356\,111\,039\,402 \quad \text{and} \\ M_n &= 9 \cdot 19 \cdot 37 \cdot 61 \cdot 67 \cdot 97 \cdot 103 \cdot 109 \cdot 151 \cdot 163 \\ &= 693\,110\,504\,329\,192\,503 \end{aligned}$$

4.2 Parallelism and Main Loop

Each processor core was assigned an interval of t_p values to process by giving it values of H^- and H^+ .

For finding pseudosquares, $H^+ - H^- \approx M_n \cdot 4.76 \times 10^{11}$. For finding pseudocubes, $H^+ - H^- \approx M_n \cdot 4.99 \times 10^{12}$.

Parallelism was achieved by having different processors working on different intervals simultaneously. Once all processors had finished their current intervals, the work was saved to disk (allowing restarts as needed) and new intervals were assigned.

To process an interval, each processor core did the following:

1. Using the wheel datastructure, generate all square or cube values of t_p with $H^- \leq t_p M_n \leq H^+$, and store these in an array $A[]$.
2. The wheel datastructure does not generate the t_p values in order, so sort $A[]$ in memory using quicksort. Note that H^- and H^+ are chosen close enough together so that this array held no more than 40 million integers, using at most 320 megabytes of RAM per processor core.
3. Using the first and last entries in $A[]$, compute a range of valid t_n values to process, and then use a wheel datastructure to generate all t_n values in that range such that $-t_n$ is square modulo M_n for pseudosquares, or t_n is a cube modulo M_n for pseudocubes.

We use an outer loop over t_n values in the order enumerated by the wheel data structure for M_n , and an inner loop over consecutive t_p values drawn from $A[]$.

4. For each t_n generated, we normalize sieve tables for the next 4 primes (101, 103, 107, 109 for pseudosquares, and 193, 199, 211, 223 for pseudocubes) to allow for constant-time table lookup to see if an x -value (see below) is a square/cube modulo these primes, indexed by t_p value.

The number of primes to use for this depends on how many t_p values will be processed for each t_n – in our case, it was several hundred on average, so this step improves performance. If it were fewer, say 50, then normalizing the sieve tables would require more work than is saved by having constant-time lookup.

5. For each t_n generated, using binary search on $A[]$ to find all the t_p values it can match with, generate an $x = t_p M_n - t_n M_p$ within our global search

range. (For example, in our last run for pseudosquares, we searched for x values between 7.5×10^{24} and 10^{25} .)

Note: at this point we do not actually compute the value of x .

6. Lookup each t_p value in the normalized tables mentioned above. If it fails any of the 4 sieve tests, move on to the next t_p value. For pseudosquares, a t_p value passes these tests with probability roughly $(1/2)^4 = 1/16$, and for pseudocubes, roughly $(1/3)^4 = 1/81$.

Note that this step is the running time bottleneck of the algorithm.

7. The next batch of primes q have precomputed sieve tables that are not normalized, but we precompute M_p and M_n modulo each q so we can compute $x \bmod q$ without exceeding 64-bit arithmetic. Continue only if our t_p value passes all these sieve tests as well. The expected number of primes q used in this step is constant.
8. Finally, compute x using 128-bit hardware arithmetic, and see if it is a perfect square or perfect cube. If it passes this test, append x to the output file for this processor core.

We had two wheel datastructures, one each for M_p and M_n . For details on how this datastructure works, see [9]. We leave the details for how to modify the datastructure to handle cubes in place of squares to the reader.

4.3 Implementation Details

To compute the tables presented in §2, we used Butler University’s cluster supercomputer, *BigDawg*, which has 24 compute nodes, each of which has four AMD Opteron 8354 quad-core CPUs at 2.2GHz with 512KB cache, for a total of 384 compute cores. As might be expected, we did not have sole access to this machine for over a year, so the code was designed, and ran, using anywhere from 10 to 24 nodes, or from 160 to 384 cores, depending on the needs of other users. This flexibility is one advantage of our parallelization method – by t_p intervals. In [12], they parallelized over residue classes, which restricts the CPU count to a fixed number (180 in their case).

BigDawg runs a Linux kernel on its head node and compute nodes, and the code was written in C++ using the gnu compiler (version 4.1.2) with MPI. It has both 10GB ethernet and Infiniband interconnect, but inter-processor communication was not a bottleneck for our programs.

We tested our code by first finding known pseudosquares (all but the highest few) and known pseudocubes, in the process verifying previous results.

5 Future Work

We plan to port our code to work with 8 NVidia GPUs recently added to Butler’s supercomputer, giving it roughly 2-3 times the raw computing power. This will require a major restructuring of the code, and the removal of recursion in the wheel datastructure.

References

1. Agrawal, M., Kayal, N., Saxena, N.: PRIMES is in P. *Ann. of Math.* (2) 160(2), 781–793 (2004), <http://dx.doi.org/10.4007/annals.2004.160.781>
2. Bernstein, D.J.: Doubly focused enumeration of locally square polynomial values. In: *High primes and misdemeanours: lectures in honour of the 60th birthday of Hugh Cowie Williams*, Fields Inst. Commun., vol. 41, pp. 69–76. Amer. Math. Soc., Providence, RI (2004)
3. Bernstein, D.J.: Proving primality in essentially quartic random time. *Math. Comp.* 76(257), 389–403 (electronic) (2007), <http://dx.doi.org/10.1090/S0025-5718-06-01786-8>
4. Berrizbeitia, P., Müller, S., Williams, H.C.: Pseudocubes and primality testing. In: *Algorithmic number theory, Lecture Notes in Comput. Sci.*, vol. 3076, pp. 102–116. Springer, Berlin (2004)
5. Hardy, G.H., Wright, E.M.: *An Introduction to the Theory of Numbers*. Oxford University Press, 5th edn. (1979)
6. Lukes, R.F., Patterson, C.D., Williams, H.C.: Some results on pseudosquares. *Math. Comp.* 65(213), 361–372, S25–S27 (1996)
7. Pomerance, C., Shparlinski, I.E.: On pseudosquares and pseudopowers. In: *Combinatorial number theory*, pp. 171–184. Walter de Gruyter, Berlin (2009)
8. Schinzel, A.: On pseudosquares. *New Trends in Prob. and Stat.* 4, 213–220 (1997)
9. Sorenson, J.P.: The pseudosquares prime sieve. In: Hess, F., Pauli, S., Pohst, M. (eds.) *Proceedings of the 7th International Symposium on Algorithmic Number Theory (ANTS-VII)*. pp. 193–207. Springer, Berlin, Germany (July 2006), LNCS 4076, ISBN 3-540-36075-1
10. Stephens, A.J., Williams, H.C.: An open architecture number sieve. In: *Number theory and cryptography (Sydney, 1989)*, London Math. Soc. Lecture Note Ser., vol. 154, pp. 38–75. Cambridge Univ. Press, Cambridge (1990)
11. Williams, H.C.: *Édouard Lucas and primality testing*. Canadian Mathematical Society Series of Monographs and Advanced Texts, 22, John Wiley & Sons Inc., New York (1998), a Wiley-Interscience Publication
12. Wooding, K., Williams, H.C.: Doubly-focused enumeration of pseudosquares and pseudocubes. In: *Proceedings of the 7th International Algorithmic Number Theory Symposium (ANTS VII)*. Berlin, Germany (2006)